

FFX52507ZW

Natural drying with fresh air. For perfectly dry dishes

The 3000 AirDry Dishwasher maximises drying using natural airflow. The door automatically opens 10 cm in the final stage of the cycle, drying dishes naturally and effectively. Dishes dry 3x better than closed-door systems.

Product Benefits & Features



Open the door to dry dishes AirDry delivers up to 3x better drying performance when compared to closed-door systems. The door automatically opens at the end of the drying phase and air is circulated inside the machine. Dishes emerge perfectly dry. Every time.



Customisable space and convenient cleaning with MaxiFlex

The MaxiFlex drawer is engineered to accommodate cutlery and utensils of many sizes, whether large or awkwardly shaped. Flexible dividers and maximised depth mean each load is customisable. Essentially every item is seamlessly loaded and cleaned in one go.

Water reaches every corner. With the Dual Spray Arms

Ensure maximum water coverage with two spray arms. The rotating sprinklers send water jets into every corner of both the lower and upper basket, for dishwashing results you can rely on.

Fast and efficient performance

This dishwasher gives you perfect performance - fast, thanks to its special halfhour program.

Rinse off your dishes when the dishwasher is not yet full

When your dishwasher is only half full, you may want to wait before you run a full cycle. The Rinse & Hold program quickly rinses partial loads of dirty dishes, minimising unpleasant smells and keeping bacteria at bay.

- Capacity: 10 Place Settings
- Multi-tab
- Delay StartHeight Adjustable Upper Basket

5000 AirDry Dishwasher 45cm

FFX52507ZW

AEG

Product Specification	
Series	5000
Energy Rating	E
Number of Place Settings	10
Dishwasher Programs	160 Minutes, 90 Minutes, ECO, Quick 30 Minutes, Rinse & Hold
Indicators	Rinse aid, Salt, On/off, Delay start 3h, Drying phase, Ok/Start, Rinse phase, Washing phase
Drying System	AirDry Technology
Noise Rating (dB)	С
Dimensions (mm) (HxWxD)	850x446x615
Built-in Dimensions (mm) (HxWxD)	820-850x450x570
Water Supply	Cold or hot
Cord Length (m)	1.5
Inlet Hose Length (cm)	150
Outlet Hose Length (cm)	150
Total Electricity Loading (W)	1950
Wheels/Feet	4 adjustable feet (adj 0 to 3cm)
Voltage (V)	220-240
Required Fuse (A)	10
Frequency (Hz)	50
Number of Programmes	5
Number of Temperatures	3
Door Colour	White
Upper Spray Arm Type	Dual spray arms

Lower Spray Arm Type	Standard
Inlet Pipe Type	Standard hot
Anti-flood Device Type	Floating switch
ProdPartCode	B - Open All
Noise (dB)	46
Energy Consumption per 100 wash cycles (kWh)	75
Culterly Basket	No
Cutlery Drawer	Knife rack holder, MaxiFlex Drawer, Removable dividers

