

Audio Technica LP120XBTUSB Technical Data

- Type - 3-speed, fully manual operation
- Motor - DC servo motor
- Drive Method - Direct drive
- Speeds - 33-1/3 RPM, 45 RPM, 78 RPM
- Turntable Platter - Die-cast aluminum
- Starting Torque - >1.0 kgf.cm
- Braking System - Electronic brake
- Wow and Flutter - <0.2% (WTD) @ 3 kHz (JIS)
- Signal-to-Noise Ratio - >50 dB
- Output Level - Pre-amp "PHONO": 4 mV nominal at 1 kHz, 5 cm/sec, Pre-amp "LINE": 240 mV nominal at 1 kHz, 5 cm/sec
- Phono Pre-Amp Gain - 36 dB nominal, RIAA equalized
- USB Function - A/D, D/A – 16-bit/44.1 kHz or 48 kHz USB selectable; Computer interface – USB 2.0 Compliant Windows 7 or above, or MAC OS X or above
- Power Supply Requirements - 100 to 240 V, 50/60 Hz, 1.5A Max
- Power Consumption - 2.75 W
- Dimensions – 452.0 mm (17.80") W x 352.0 mm (13.86") D x 141.6 mm (5.57") H
- Weight - 8 kg (17.6 lbs.), without dust cover
- Tonearm Type - Balanced S-shaped tonearm with detachable headshell
- Effective Arm Length - 230.5 mm
- Overhang - 16 mm
- Tracking Error Angle - Less than 3 degrees
- Applicable Cartridge Weight - 3.5-8.5 g
- Anti-skating Range - 0-4 g
- Replacement Stylus - AT-VMN95E
- Communication System - Bluetooth Version 5.0
- Maximum Communication Range - Line of sight - approx. 10 m (33')
- Compatible Bluetooth Profile - A2DP
- Support Codec - SBC, Qualcomm® aptX™ audio