



Open the door to natural drying

The Series 20 AirDry dishwasher automatically opens the door in the final part of the cycle, letting fresh air inside – performing three times better than our closed-door systems. Automatic drying, with no extra effort from you. Just unload when it suits your schedule.

Product Benefits & Features



Three times better drying, with AirDry

AirDry technology lets air into the dishwasher in the last phase of the drying process. The door will automatically open to allow a 10cm gap, for up to three-times better drying, compared to our closed-door systems.

- Freestanding
- Capacity: 9 place settings
- Number of programmes: 5
- Height adjustable upper basket
- Foldable cup shelves
- Salt & rinse aid indicators
- Rinse and hold
- A class cleaning performance
- A class drying performance
- 3 hours delay start



Every dish clean thanks to dual spray arms

Get your dishes glistening with rotating dual spray arms that make sure water thoroughly washes plates and glasses inside and out on both the dishwashers upper and lower basket for sparkling results.



Quick cycle, to suit your schedule

The Quick programme is ideal when you're short on time, with light loads treated in just 30 minutes. Clean dishes, on your schedule.

Rinse and hold pre-washing keeps your dishwasher fresh

If it takes you a few days to fill up the dishwasher, the rinse and hold programme will prevent the build-up of odours in the meantime. Water jets remove food remnants from plates and glassware, making sure the kitchen stays fresh.

Product Specification

Installation	Built under (removable worktop)	Dishwasher programs	160 Minutes, 90 Minutes, ECO, Quick 30 Minutes, Rinse & Hold
Construction type	Free-Standing	ProdPartCode	All Open
Dimensions (mm) (HxWxD)	850x446x615	Noise Level	49
Built-under installation dimensions, mm (HxWxD)	820-850x450x570	Maximum number of place settings (EU 2017/1369)	9
Double Hinges	Normal	Weighted energy consumption in kWh per 100 washing cycles of eco 40-60 programme (EU 2017/1369)	78
Water Supply	Cold or hot	The water consumption of the eco programme in liters per cycle (EU 2017/1369)	9.9
Cord Length	1.5	Cleaning performance index (EU 2017/1369)	1.121
Inlet hose length (mm)	150	Drying performance index (EU 2017/1369)	1.061
Outlet hose length (mm)	150		
Connected load (W)	1950		
Wheels/feet	4 adjustable feet;Adj 0 to 3 cm		
Voltage (V)	220-240		
Required Fuse	10		
Frequency (Hz)	50		
Number of programmes	5		
Number of Temperatures	3		
Door Colour	White		
Anti-flood Device	Floating switch		
Inlet Pipe Type	Standard hot		
Spray arm	Standard		
Top spraing level	None		
Options	None		
Drying System	AirDry Technology		

